

Amber Covert C300

GPS VEHICLE TRACKER



GPS+LBS positioning




Smart In-App/Web
Portal Notifications

3G

WCDMA + GSM



Remote Immobilization



IPX5 Dust And Water
Proof



Vehicle Battery
Protection



Tamper alert



Intelligent Power
Management



9-90v Voltage
Range



ACC Detection
For Ignition Status

1. Download app from playstore/appstore

2. Turn on the device

3. Create account and scan your QR code

4. Go for a ride - you are connected!

GSM Specification



| | |
|----------------------|--------------------------------------------------------|
| Communication System | WCDMA/GSM |
| Frequency | WCDMA 850/900/1800/2100MHz GSM 850/900/1800/1900MHz |
| GPRS | Class 12, TCP/IP |
| Memory | 32 + 32 Mb |
| Max output | GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm |
| Max frequency error | ±0.1ppm |


GPS Specification


| | |
|-------------------------|----------------------------------------------|
| GPS chipset | BDS + AT6558 |
| Frequency | L1,1575.42MHz C/A code |
| GPS channel | 66 |
| Location accuracy | <10 meters |
| Tracking sensitivity | -162dBm |
| Acquisition sensitivity | -148dBm |
| TTF (open sky) | Avg. hot start=<1sec, Avg. cold start+<32sec |


Functional and Package

| | |
|-------------------------|-----------------------------------|
| Standby current | 5mA/12VDC |
| Battery | 400mAh/3.7V |
| LED indicator | GPS(blue), GSM(green), Power(red) |
| Working voltage/current | 9-36VDC/31mA(12VDC) 18mA(24VDC) |
| Operating Temperature | -20°C~+70°C |
| Dimension | 88(L) ×45 (W) ×13 (H) mm |
| Weight | 60g |

Need help? Contact 24/7 live support!

 In App Chat

 support@amberconnect.com

 Chat via website www.amberconnect.com

Works with Android phones and tablets, iPhone, iPad.

Compatible with Chrome, Mac and PC web browsers.



Amber Connect

Scan this QR code to download your App

©2024 Amber Connect Limited. All rights reserved.