

Amber Guard C210

Personal GNSS Tracker



GPS & WiFi & LBS Positioning

A synergy of multiple positioning systems ensures the locations to be accurately displayed on cloud platform.



Panic Button You can press this button to send an immediate alert for emergency help or rescue.



Geo-fence

A virtual area set on platform by yourself, you'll be informed when the person crossing its boundary.



Remote Listen-in An inconspicuous Mic allows you to remotely listen In the sounds around the device.

(≩)

Two-way Communication

Enable you to make call with this device by

your mobile phone.

Low Battery Alert

You'll be alerted when the remaining battery has

reached threshold.



IPX5 Water Resistance Rugged and reliable design ensures normal functioning in different weather conditions.



Compact Size Light and small design makes this device easy-to-carry.

Personal GNSS Tracker

The AGC210 personal GPS tracking device will give you a completely new level of awareness and convenience. It's compact, lightweight design is both highly mobile and highly reliable. Loaded with GPS and LBS positioning, AGC210 enables you to view real-time location from a computer, tablet or smartphone. Being stylish, tough and accurate, the AGC210 is an ideal for kids the elderly, and people with special needs.





Module

Name	AGC 210
Technology	GNSS/GPRS/GPS/BLUETOOTH

GNSS

Positioning system	GPS+WiFi+LBS
Frequency	L1
Positioning accuracy	<2.5mCEP
Track sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTFF (open sky)	Avg. hot start ≤ 1 sec Avg. cold start ≤32sec

Cellular

Communication network	GSM
Frequency	Quad-band 850/900/1800/1900 MHz



Power

Battery	500mAh/3.8V industrial-grade Li-Polymer battery	
Working modes	Mode 1 : WiFi regular-upload mode Mode 2: GPS tracking mode	
Standby time	Up to 2 days if upload WiFi positions per 10 minutes	

Interface

LED indication	GNSS (Blue), Cellular (Green), Power (Red)	
SIM	Nano-SIM	
Data storage	64Mb	

Physical specification

Dimensions	45.0 × 45.0 × 16.0 mm
Weight	33g

Operating environment

Operating temperature	-20°C to +60°C
Operating humidity	5% ~ 95%, non-condensing
IP rating	IPX5

Feature

Voice monitoring range	<3 meters	
Sensors	Accelerometer	Let ESV
Scenarios	Low battery alert, SOS alert, Geo-fence	
Specialties	Two-way Communication, Audible-and-visual recovery	



In App Chat

Need help? Contact 24/7 live support!

Works with Android phones and tablets, iPhone, iPad. Compatible with Chrome, Mac and PC web browsers.







Scan this QR code to download your App

©2024 Amber Connect Limited. All rights reserved.