

Amber Guard T200

Mini Tracker Easy



ALARM BUTTON

Easy to reach, instant messaging in case of emergency



LIVE TRACKING

Real time monitoring of employee location



INSIDE TRACKING

Get a live tracking information from inside the buildings with the help of BLE beacons



MAN DOWN & NO MOVEMENT EVENT

Automated emergency alarm for no movement scenarios



EXTRA SMALL

Dimensions only 44x43x20 mm. Such a device can be easily hidden and work for long hours



BLE BEACON SUPPORT

Low power sensors and BLE Beacon support for various use cases

Amber Guard T200 Mini Tracker Easy

Amber Guard T200 is an autonomous personal tracker with GNSS, GSM and Bluetooth connectivity. Our mini tracker is designed for the monitoring of people, pets and cars. It can also be applied for employee control, security staff at the sport events and other use cases to ensure security and control. IP67 waterproof case provides convenient usage, even in harsh conditions. The large battery's capacity expands the application range where long battery life is needed. Also, Amber Guard T200 supports firmware and configuration update via Fota WEB.

Use Cases



Workers



Offices &
Bank Security



Driver Security



School children



Pets, Farm
Animals

Module

Name	ART 200
Technology	GSM/GPRS/GNSS/Bluetooth (4.0 + LE)

GNSS

GNSS	GPS, GLONASS, GALILEO, BEIDOU, QZSS, AGPS
Receiver	Tracking: 33
Tracking sensitivity	-165 dBm
Position accuracy	< 2.5 CEP
Hot start	< 1 s
Warm start	< 25 s
Cold start	< 35 s

Cellular

Cellular technology	GSM
2G bands	Quad-band 850 / 900 / 1800 / 1900 MHz
Data transfer	GPRS Multi-Slot Class 12(up to 240 kbps) GPRS Mobile Station Class B
Data support	SMS (text/data)

Power

Power	3.8 V 800 mAh rechargeable Li-ion battery
-------	---

Interface

GNSS antenna	Internal High Gain
Cellular antenna	Internal High Gain
Bluetooth antenna	Internal High Gain
Sensors	Accelerometer
USB	4 pin magnetic USB Cable
Interface	ART200 module, Internal Micro-SIM Slot, 128 MB internal flash memory (220'000 records)
Buttons	2 configurable buttons
Indication	RGB LED, Vibration

Features

Configuration and firmware update	FOTA WEB (cloud based solution), Amber Configurator (USB, Bluetooth), Configuration through SMS
Scenarios	Alarm button, Man-down detection, Home zone, Inside tracking, Movement/No Movement Events, 50 Manual Geofence zones, Over Speeding, Action on call feature, Real Time tracking, Smart algorithm of GPRS data sending for GPRS traffic saving, Asset tracking
Sleep modes	Online Deep Sleep, Deep Sleep, Ultra Deep Sleep, Low power mode
Protocols	UDP/TCP/SMS
Data sending	Primary, Duplicate and Backup servers
Security	Configuration password, SMS login and password, Authorized GSM numbers list, TLS
Time Synchronization	GNSS, NITZ, NTP
Supported peripherals	Bluetooth LE Movement sensors, LE Magnet sensors, LE Temperature and Humidity sensors and LE Temperature sensors support, iBeacon and Eddystone beacon support.

Physical specification

Dimensions	44 × 43 × 20 mm (L x W x H)
Ingress Protection Rating	IP67


Certification & approvals


Regulatory	CE/RED, EAC, RoHS, REACH, ANATEL (pending), UKCA (pending)
------------	--



Need help? Contact 24/7 live support!

 In App Chat

 support@amberconnect.com

 Chat via website www.amberconnect.com

Works with Android phones and tablets, iPhone, iPad.

Compatible with Chrome, Mac and PC web browsers.



Amber Connect

Scan this QR code to download your App

©2024 Amber Connect Limited. All rights reserved