

Amber Swift C210

Wireless GPS Tracker



GPS & WiFi & LBS Positioning

A synergy of multiple positioning systems ensures the locations to be accurately displayed on cloud platform.




10,000mAh Rechargeable Battery

Allows ultra-long standby time, also the device can be redeployed after charging.



IPX5 Water Resistance

Rugged and reliable design ensures stable operation in tough conditions.



Remote Listen-in

An inconspicuous Mic allows you to remotely listen in the sounds around the device.



Tamper Alert

When the pressure-sensitive button is loose, you'll get notified of device removal.



Strong Magnetic Base

Can be attached on metallic surface tightly. If it is tampered with, the device will trigger an alert.

Long-standby Asset GNSS Tracker

The advanced features rugged construction, and industry-leading battery life make the ASC210 the new state of the art in asset GPS tracking. Using GPS and LBS positioning, the magnet-mounted ASC210 gives detailed reports telling you exactly where a vehicle has been, where it's headed and how fast it's traveling. The internal mic allows for audio monitoring of the environment. With a 10000mAh battery and IPX5 waterproof rating, the ASC210 puts you in total control of individual vehicles or fleets.



Vehicle Rental



Fleet Management



Logistics

Module

Name	ASC 210
Technology	GSM/GPRS/GPS/BLUETOOTH

GNSS

Positioning system	GPS+Wifi+LBS
Frequency	L1
Positioning accuracy	<2.5mCEP
Track sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTFF (open sky)	Avg. hot start ≤ 1 sec Avg. cold start ≤32sec

Cellular

Communication network	GSM
Frequency	Quad-band 850/900/1800/1900 MHz

Power

Battery	1 0.000mAh/3. 7V industrial-grade Li-Polymer battery
Working modes	Mode 1 : Tracking mode Mode 2: Power-saving mode
Standby time	Up to 2.5 years in power-saving mode

Interface

LED indication	1 status indicator (Red), 4 battery indicators (Blue)
SIM	standard-SIM
Data storage	32+32Mb
Tamper proof	Pressure-sensitive button

Physical specification

Dimensions	108.0 × 61.0 × 30.0 mm
Weight	285g

Operating environment

Operating temperature	-20°C to +70°C
Operating humidity	5% ~ 95%, non-condensing
Ingress Protection Rating	IPX5

Feature

Sensors	<3 meters
Sensors	Accelerometer
Scenarios	Low battery alert. Tamper alert. Vibration alert. Over-speed alert. Cover removal alert. Power off alert. Geo-fence.



In App Chat

support@amberconnect.com

Chat via website www.amberconnect.com

Works with Android phones and tablets, iPhone, iPad.
Compatible with Chrome, Mac and PC web browsers.



Amber Connect

Scan this QR code to download your App

©2024 Amber Connect Limited. All rights reserved.