


Amber Vision C410

Dual 4G Telematics HD Dashcam with Driver Monitoring AI



Driving Behavior Analysis

The dashcam can detect the driver's dangerous driving practices such as harsh acceleration, harsh braking, etc.



Panic Button

This enables the driver to call for help in emergencies.



Real-Time Tracking

The video recorder can be used as a tracker to locate the vehicle and collect and upload data such as speed and time in real-time.



Various Communication Standards

It is able to communicate via 2G/3G/4G, Wifi, and Bluetooth.



DMS

The DMS camera is able to align the driver's face and alert the driver and the backoffice manager if risk behaviors such as drowsy driving and smoking while driving are detected.



Event Video to Cloud

Videos triggered by a collision, vibrating, SOS call, and other exceptions will be auto uploaded to the cloud.

Let A.I. Enhance Your Fleet Management

The Amber Vision C410 is the highest-level integrated video telematics solution for fleets. Using high-end DMS technology, you can capture what matters most, coach your drivers mitigate risk, defend against fraudulent insurance claims and protect your business' reputation. The Amber Vision C410 4G dash cam works independently of any phone or hotspot, allowing for reliable and smooth recording on the road.

Specifications

Network Connection

| | |
|-----------------------------|---|
| WiFi | 2.4GHz, 802.11 b/g/n |
| BT | BLE 4.0 |
| Amber Vision C410-E | GSM: 850/900/1800/1900MHz WCDMA: B1/B2/B5/B8 FDD LTE: B1/B3/B5/B7/B8/B19/B20 TDD LTE: B38/B39/B40/B41 (100M) |
| Amber Vision C410-LA | GSM: 850/1800/1900MHz WCDMA: B2/B4/B5 FDD LTE: B2/B3/B4/B5/B7/B12/B17 TDD LTE: B38/B41 (100M) |

Configuration

| | |
|----------------|--|
| CPU | Quad-core 1.4GHz A53 |
| OS | Android 8.1 GO |
| GNSS | GPS+BDS |
| G-Sensor | 6-oxls |
| Mic | ✓ |
| Speaker | ✓ |
| Data Interface | Micro USB 2.0 |
| Memory | TF card (Max. 256GB) |
| SIM Card | Micro or Nano |
| LED | Red (Power), Blue (Cellular), Green (GNSS) |

Camera

| | |
|--------------|--|
| Main Unit | Front camera: 1920x 1080/25FPS/F2.2/full color |
| Subcamera | DMS camera: 1280x720/10FPS/F2.0/monochrome all day |
| Image Format | H.264 |

Specifications


Others


| | |
|-----------------------|-------------------------|
| Battery | External: 450mAh |
| Power Supply | Power cable: B+/ACC/GND |
| Operating Temperature | -20°C to +65°C |
| Operating Voltage | 9-30V DC |
| Device Weight | 233g |
| Device Dimension | 109x69x52mm |
| Certifications | FCC/CE/RoHS |



Need help? Contact 24/7 live support!

 In App Chat

 support@amberconnect.com

 Chat via website www.amberconnect.com

Works with Android phones and tablets, iPhone, iPad.

Compatible with Chrome, Mac and PC web browsers.



Amber Connect

Scan this QR code to download your App

©2024 Amber Connect Limited. All rights reserved.